

Three Phase Hybrid Inverter

SUN- 8 / 10 / 12 K-SG04LP3

KE Solar

نیرویی برای فردایی روشن‌تر



Deye

Clean Power For You

100%

100% unbalanced output, each phase
Max. output up to 50% rated power

48

48V low voltage battery, transformer isolation design

6

6 time periods for battery charging/discharging

240

Max. charging/discharging current of 240A

16

Frequency droop control, Max.16pcs parallel



DC couple and AC couple to retrofit existing solar system



Support storing energy from diesel generator

Model	SUN-8K-SG04LP3	SUN-10K-SG04LP3	SUN-12K-SG04LP3
Battery Input Data			
Battery Type	Lead-acid or Li-Ion		
Battery Voltage Range (V)	40~60V		
Max. Charging Current (A)	190A	210A	240A
Max. Discharging Current (A)	190A	210A	240A
Charging Curve	3 Stages / Equalization		
External Temperature Sensor	Optional		
Charging Strategy for Li-Ion Battery	Self-adaption to BMS		
PV String Input Data			
Max. DC Input Power (W)	10400W	13000W	15600W
PV Input Voltage (V)	550V (150V~800V)		
MPPT Range (V)	200V-650V		
Start-up Voltage (V)	160V		
PV Input Current (A)	13A+13A	26A+13A	26A+13A
No.of MPPT Trackers	2		
No.of Strings Per MPPT Tracker	1+1	2+1	2+1
AC Output Data			
Rated AC Output and UPS Power (W)	8000W	10000W	12000W
Max. AC Output Power (W)	8800W	11000W	13200W
Peak Power (off grid)	2 times of rated power, 10 S		
AC Output Rated Current (A)	12A	15A	18A
Max. AC Current (A)	18A	23A	27A
Max. Continuous AC Passthrough (A)	50A		
Output Frequency and Voltage	50/60Hz; 230/400Vac (Three phase)		
Grid Type	Three Phase		
Current Harmonic Distortion	THD<3% (Linear load<1.5%)		
Efficiency			
Max. Efficiency	97.60%		
Euro Efficiency	97.00%		
MPPT Efficiency	99.90%		
Protection			
PV Input Lightning Protection	Integrated		
Anti-islanding Protection	Integrated		
PV String Input Reverse Polarity Protection	Integrated		
Insulation Resistor Detection	Integrated		
Residual Current Monitoring Unit	Integrated		
Output Over Current Protection	Integrated		
Output Shorted Protection	Integrated		
Output Over Voltage Protection	Integrated		
Surge protection	DC Type II / AC Type II		
Certifications and Standards			
Grid Regulation	IEC61727, IEC62116, IEC60068, IEC61683, NRS 097-2-1		
Safety EMC / Standard	IEC62109-1/-2, IEC61000-6-1, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12		
General Data			
Operating Temperature Range (°C)	-25~60°C, >45°C Derating		
Cooling	Smart cooling		
Noise (dB)	<30 dB		
Communication with BMS	RS485; CAN		
Weight (kg)	36.8		
Size (mm)	422W×658H×281D		
Protection Degree	IP65		
Installation Style	Wall-mounted		
Warranty	5 years		