



Wall Mounted Solar Battery

RZE-51314LI-TS



Safe & Reliable



6000+ cycles @%80 DOD
and 5 years warranty.



Modular design
without mounting bracket.



One key on/off,
redundancy protection.



Live communication, and compatible with most leading LV inverters.

GOODWE

Deye 德業®

GROWATT

victron energy

SMA

Voltronk Power

SUNGROW

SRNE

EPEVER



Rizon Technologies

75-71, Shelton Street, Covent Garden, London, WC2H9JQ, UNITED KINGDOM

+442081871184

info@rizontechnologies.com

۰۲۱۹۱۰۳۰۸۲۰ | www.ke-solar.com

© 2023 Rizon Technologies. All rights reserved



RZE-51314LI-TS

Battery Module	RZE-51314LI-TS
Battery category	LiFePO4
Rated energy (kWh) (25 °C, 0.5C)	16.076
Rated voltage (V)	51.2
Rated capacity (Ah)	314
Max. charging and discharging current (A)	200
Charging and discharging current (A)	100 (Recommended)
Dimension (W*D*H, mm)	754*480*249.5
Weight (Kg)	126
Operating voltage (V)	43.2V-58.4V
Working temperature	0 °C ~ 45 °C , Recommend 15 °C ~ 30 °C
Communication	CAN/RS485/WIFI
Degree of protection	IP20

■ Products specifications described herein are subject to change without prior notification.