

RIZON >>>>

Hybrid Solar Inverter 4kw/6kw

Rodimus series

- Detachable LCD control module with various communications
- Maximum PV input current 27A
- Dual output for smart load management
- Built-in WiFi for mobile monitoring (App is available)
- Supports USB On-the-Go function
- Reserved communication port (RS485, CAN-BUS or RS232) for BMS
- Battery independent design
- Battery equalization extends lifecycle
- User-friendly LCD operation
- Replaceable fan design for ease of maintenance

x2
Dual
outputs



RZE4K#24VH



RZE6K#48VH

MODEL	RZE4K#24VH	RZE6K#48VH
RATED POWER	4000VA/4000W	6000VA/6000W
INPUT		
Voltage	230 VAC	
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation (Batt. Mode)	230VAC ± 10%	
Surge Power	8000VA	12000VA
Efficiency (Peak)	90~93%	
Transfer Time	10 ms (For Personal Computers) 20 ms (For Home Appliances)	
Waveform	Pure sine wave	
BATTERY		
Battery Voltage	24 VDC	48 VDC
Floating Charge Voltage	27 VDC	54 VDC
Overcharge Protection	33 VDC	63 VDC
SOLAR CHARGER & AC CHARGER		
Solar Charger type	MPPT	
Maximum PV Array Power	5000W	6000W
MPP Range @ Operating Voltage	60 ~ 450 VDC	
Maximum PV Array Open Circuit Voltage	500 VDC	
Maximum PV Input Current	27A	
Maximum Solar Charge Current	120A	
Maximum AC Charge Current	100A	
Maximum Charge Current	120A	
PHYSICAL		
Dimension, D x W x H (mm)	115 x 300 x 435	
Net Weight (kgs)	9	10
Communication Interface	USB/RS232/RS485/WiFi/Dry-contact	
OPERATING ENVIRONMENT		
Humidity	5% to 95% Relative Humidity (Non-condensing)	
Operating Temperature	-10°C to 50°C	
Storage Temperature	-15°C to 60°C	



75-71, Shelton Street, Covent Garden, London, WC2H 9JQ, UNITED KINGDOM

info@rizontechnologies.com rizontechnologies.co.uk

@2023rizontechnologies. All rights reserved.